


## ▶ TABLE OF STANDARD PROPERTIES OF USE AND MEASUREMENT

The properties defined in the table below, are set up according to the technical conditions of use and measurement. These properties are warranted within their variation range and in compliance with the standard technical conditions of use.



NON-CONTRACTUAL PICTURE

PROPERTIES	STANDARD TECHNICAL CONDITIONS	UNIT	NOMINAL VALUES	MIN. VALUES	MAX. VALUES
Notes			Preliminary data		
Base			APA35XS		
Mastered motions			TX		
Max. No-load displacement		mm	10.00	9.00	11.00
Holding force without consumption		N	3.00	2.01	3.99
Max speed	Unloaded, with adapted driver	mm/s	30.00	18.00	39.00
Max step size	Unloaded, with adapted driver	μm	37.50	22.50	48.75
Max driving force		N	1.00	0.80	1.20
Typical max loading		gr	70.00	49.00	77.00
Typical working frequency		Hz	800.00	720.00	880.00
Typical stepping mode resolution		μm	1.00	0.90	1.10
Deformation stroke	Quasistatic excitation, blocked-free	μm	55.00	49.50	71.50
Linear resolution		nm	0.55	0.33	0.72
Stiffness	Harmonic excitation, blocked-free, on the admittance curve	N/μm	0.49	0.39	0.54
Capacitance		μF	0.25	0.23	0.33
Voltage range		V	-20 ... 150		
Out of plane		μm	6.00	5	7
Z rotation		μrad	0.30	0.24	0.36
X Y rotation		μrad	0.30	0.24	0.36
Typical Lifetime	Unloaded, 2mm stroke, full speed, 50% duty-cycle	cycles	1000000.00	700000	1400000
Sensors option			MAG		
Height		mm	15.00	13.50	16.50
Width		mm	30.00	27.00	33.00
Length		mm	30.00	27.00	33.00
Mass		g	30.00	27.00	33.00
Unloaded resonance frequency (in the actuation's direction)	Harmonic excitation, blocked-free, on the admittance curve	Hz	900.00	765.00	990.00
Mechanical interfaces (payload)			4 x M2 deep. 6		
Mechanical interfaces (frame)			4 x diam 2.4 holes		
Electrical interfaces			8 pins ERNI connector		

## ➤ LSPS35XS CONFIGURATION

